



SAFETY CHECK AND REGISTRATION FORM

Safety Decal Serial Number _____

Car Related Items

Roll Cage

(Minimum 1" to drivers helmet) _____
(DQ) Seat/Shoulder Belts _____
Shoulder, Seat, & Crotch belt required _____

(4year maximum, SFI 16.1, Anti-Sub
Nerf Bars/Bumpers _____
(Minimum (2) 6/32 bolts, Grade 5 min.)
Min 3 bolts for Nerfs

Shoulder Bar _____
(Min.8/32 bolt at spud or clamp grade 5 min)

(DQ)**Axles/Hubs** _____
(Axles not past wheels.)

Belly Pan _____
(Minimum gauge 0.040 AL, No open holes

Fire Wall _____
(Minimum gauge 0.048 AL, No open holes

(DQ)**Steering Wheel** _____
(1" thick, 2" diameter pad, min.)

Steering _____
(No over center, binds) _____
inches)

Ignition System _____

Brakes

(DQ)(Heel Stop, Metallic outer shield brake line) _____

Fuel System

(Minimum quality wire tie clamp) _____

Fuel Line - Rated for Gasoline or Methanol _____

Fuel Sleeve - Fire Resistant Sleeve _____

(DQ required on all fuel lines) _____

Fuel Filter - Steel or Aluminum Only _____

(DQ)**Exhaust System** _____

Throttle Cable

(No binding) _____

Tail Cone

(Below top of bumper) _____

Tires/Wheels

(Three lug nuts) _____

(DQ) **Oil Catch Can** _____

(Located under tail)

(DQ) **Weights** _____

(No weights fastened to side pod sheet metal, lead weights must be bolted and coated or wrapped in white or bright color, last name on each piece, 1.5" min fender washers must be included if its bolted through belly pan. 2 bolts required if weight is 6"X6" or larger)

Side Panels L _____ R _____

(2" hole for access to flywheel nut, (DQ)maximum 22

Enclosed Nose Section

DECALS _____

Hoosier, USAC, USAC.25 _____

Drivers Equipment

(DQ) **Helmet** _____

(Snell SA 2010 (or higher)or SFi24.1 (or higher)

Face Shield

(No cracks) _____

(SFI 3.2 A/1 minimum)

(DQ) **Neck Collar** _____

(Nomex or Equivalent or Head & Neck Restraint SFI 38.1 Certified)

Effective January 1, 2012, Head and Neck Restraint Systems shall be inspected for recertification every five years after the date of original certification. Product inspection, maintenance, and/or replacement procedure is per individual manufacturer. Inspection must be done by the original manufacturer only, and not their authorized resellers or dealers. When a unit is determined by the manufacturer to be acceptable for continued service and in compliance with the current version of the specification, the original manufacturer shall place on the product a new SFI 38.1 conformance label marked with the inspection date.

(DQ) **Gloves** _____

(SFI 3.3/5, 1 layer)

(DQ)**Arm Restraints** _____

(Worn close to wrist, not above elbow)

(DQ)**Suit 1 or 2 piece** _____

(SFI 3.2A/1min. no jeans)

(SFI 3.2A/5 & Head sock in Form Mod)

(DQ) **Shoes** _____

(Completely cover fee, flat bottom

General Safety Condition: _____

Safety Director Signature: _____

Registration

Date _____ Car # _____ Color _____

Class: Rookie 120 160 Mod Form Mod Animal W/F
Division: Junior Senior Light Heavy Unrestricted

Drivers Name _____ DOB: _____ Age _____

Address _____ City, State, Zip _____

Handlers Name _____ Phone _____

Address _____ City, State, Zip _____

.25 Club _____ Drivers

I agree to assume all responsibility at this event and to abide by all .25 rules/procedures.

Signature of Owner and/or Handler _____

NOTE: (DQ is reference to item that is a Disqualifiable item from race or timing event.